

MASON PROGRESSIVE CYCLES: InSearchOf 2018.

DIMENSIONS IN mm	XS [42]	S [46]	M [50]	L [54]	XL [58]
SEAT TUBE C/T	420	460	500	540	580
SEAT TUBE C/C	380	415	445	490	530
BB DROP	76	75	75	75	73
REAR CENTRE	445	445	445	445	445
FRONT CENTRE	623	629	634	644	660.4
TT EFFECTIVE	542.3	553.2	557.6	566.6	586.5
TT ACTUAL	527.3	534.3	536.4	544.7	564.7
STACK	608.3	619.3	628.3	637.7	656.8
REACH	365.8	373.8	375.7	382.0	396.6
S/O - 27.5 x 2.8 [Measured vertically, 50mm in front of BB centre]	74.0	76.5	79.0	82.5	86.5
S/O - 29 x 2.4 [Measured vertically, 50mm in front of BB centre]	76.0	78.5	81.0	84.5	88.5
OFFSET	50	50	50	50	50
TRAIL	86.1	82.6	82.6	82.6	79.0
FORK CROWN HEIGHT	483	483	483	483	483
HEAD ANGLE°	69.5°	70.0°	70.0°	70.0	70.5°
HEAD TUBE LENGTH	100	110	120	130	150
SEAT TUBE ANGLE°	74.0°	74.0°	74.0°	74.0°	74.0°
WHEELBASE	1056.7	1063.8	1068.9	1078.6	1095.3
AXLE SPACING	148	148	148	148	148
FRAME WEIGHT	2100g	2180g	2260g	2400g	2480g
FORK WEIGHT HotShoe	700g	700g	700g	700g	700g
RIDER HEIGHT GUIDE cm	151-163	162-174	170-183	180-190	188-198
STEM	70	70	80	90	100
HANDLEBAR [OUTSIDE DIMENSION]	420	420	440	440	460
CRANKARM	170	170	172.5	172.5	175